# PSU-3.5A

## Universal 12 VDC, 3.5 A power supply

### Overview

The PSU3.5A is a 3.5A 12V encapsulated power supply which is suitable for use with all TruVision and UltraView cameras.

The unit features a universal mains input voltage range from 100 to 240V ac and includes electronic short circuit protection and mains status indication. It also has high efficiency switch mode operation which means lower running temperatures and lower running costs.

The unit is specifically designed for CCTV applications, meaning it provides high reliability and performance with low maintenance and operational costs.



# PSU-3.5A

## Universal 12 VDC, 3.5 A power supply

## Technical specifications

### General

| | |
|---|---|
| Length of mains lead | Approx. 1200 mm |
| Length of output power lead | Approx. 1500 mm |
| Compatible products | TruVision Monitors |

### Output

| | |
|---|---|
| Power output voltage | 12 VDC |
| Power output current | 3.5 A |

### Electrical

| | |
|---|---|
| Mains input | 100 to 240 VAC @ 50 Hz |
| Power plug type | EU, UK |

### Physical

| | |
|---|---|
| Physical dimensions | 112 x 54 x 32mm |
| Net weight | 280 g |
| Colour | Sort |
| Form factor | Ekstern adapter |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to 40°C |
| Relative humidity | 95 % |
| Environment | Indendør |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:26