POC252-1CXP-1T

Kamera End -1-port 10/100Base-Tx koppar med PoE (at) + 1 BNC KOAX-port ej övervakningsbar mediakonverterare (-40~75 °C) – ström 48 VDC – väggmontering

Overview

The IFS® Power over Coax Network Switches and Media Converters by Interlogix® are designed to transmit both Ethernet data and PoE over coax cable up to 1 km (3,280 ft). This solution provides a cost-effective approach by reducing installation cost and increasing ROI by utilizing existing coax to migrate an existing analog video system to an IP video surveillance system.

The PoC Network Switches also provide built-in PD-alive monitor health and status of an IP camera. In addition, this solution eliminates the need for providing local power at an IP PoE camera location.



• The POC2502-8CXP-2T-2S is an 8-port Power over Coax Managed Switch that supplies data and power transmission on coax via BNC ports. In addition, the two RJ45/SFP Gigabit combo ports provide a connection to an Ethernet network.

• The POC2502-16CXP-2T-2S is a 16-port Power over Coax Managed Switch. The switch supplies data and power transmission on coax via BNC ports as well as two RJ45/SFP Gigabit combo ports for connection to an Ethernet network.

• The POC252-1CX-1P Power over Coax Media Converter is for use at the camera end to convert the data/power from the coax. The switch provides 10/100Mbps data and POE-af/at compliant power on the RJ45 port for an IP camera.

• The POC252-1CXP-1T Power over Coax Media Converter transmits data and injects power over coax for use with the POC252-1CX-1P. This is used to deploy a single IP camera on a length of coax cable and a multi-port BNC switch is not needed. This media convertor is for use at the switch end of a system.

Detaljer

- 1-port (COAX) with up to 36W power output
- Auto-negotiation and auto-MDI/MDI-X
- IEEE 1901 communication Standard
- Wavelet-OFDM modulation
- 128-bit AES security encryption
- Daisy-chain (up to 3 devices on one link)
- Half-duplex back pressure and IEEE802.3x full-duplex pause-frame flow control
- Remote power up to 1 km
- Compatible with POC252-1CX-1P (Camera End) Media Convertor

POC252-1CXP-1T

Kamera End -1-port 10/100Base-Tx koppar med PoE (at) + 1 BNC KOAX-port ej övervakningsbar mediakonverterare (-40~75 °C) – ström 48 VDC – väggmontering

Tekniska specifikationer

General

Technology	IEEE1901
Compatible with MCR rack	No

Connections


Coax ports	1
Connector	BNC
RJ45 ports	1
Port type	10/100
Fault relay output	Nej

Electrical

Power supply type	52 til 56 VDC
Redundant power	No

Physical

Colour	Sort
Mounting type	Vægmontering



Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 20:20