FC-323-WA2

Red, wall mount VAD HEAD only

The FireCell Wireless Beacon is quick and easy to install, offering individual addressing at the fire control panel. This device comprises of a sounder beacon and a wireless sounder base.

Works with FC-171-002 Red Wireless Sounder Base



Details

- 0.5 Hz / 1 Hz beacon flash selection
- Anti tamper locking mechanism
- Beacon EN54-23 coverage: W-3.1-11.3 / 396 m3
- Third party EN certified

FC-323-WA2

Red, wall mount VAD HEAD only

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	FC-171-002

Electrical

Power supply type	Batteries
Batteries	Powered by Radio Base

VAD

Colour	White Flash
Rating	W-3.1-11.3
Flash frequency	0.5 Hz / 1 Hz (selectable)

Physical

Physical dimensions	120 x 145 mm (Ø x D)
Net weight	0.65 kg
Colour	Red housing / white flash
Mounting type	Wall mount
Mounting position	Wall
Mounting base	Wireless

Environmental

Vandal proof	Yes
Operating temperature	-10 to 55 °C
Environment	Indoor

Regulatory

Compliancy	CE
Certification	BOSEC, CPR
Standards	EN54-23 EN54-13

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 12:27