PB21

2m - 360° AIR Beam Tower (double sided) including installation kit

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 2 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP4)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 20 pcs (EP4) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 2 pcs (EP4)
15. Cable gland PGM20 : 2 pcs (EP4)
16. M8x16 DIN933 : 4 pcs (TA3)
17. Side bracket <2m : 2 pcs
18. M8 DIN 985 : 4 pcs (TA3)
19. M8 DIN 125 : 4 pcs (TA3)
20. M4x12 DIN 7985 : 16 pcs (C3)
21. Bracket : 8 pcs
22. dia.2.9x16 DIN 7981 : 16 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2)



Details

- 2m height
- 360° view
- CE certified product

PB21

2m - 360° AIR Beam Tower (double sided) including installation kit

Technical specifications

General

Accessory group	Perimeter / Outdoor
Type	Mounting

Electrical

Power supply type	VDC
Operating voltage	12 to 24 V

Physical

Physical dimensions	1970 x 130 x 260 mm
Net weight	7.50 kg
Material	Aluminium, Polycarbonate / ABS

Environmental

Operating temperature	-15 to 50°C

Detection

Angle of view	360°

Output

Tamper switch	CO (change over)

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 April 2024 - 16:02