AS630

Outdoor siren with single amber beacon, inox cover

Product overview

The AS630 siren is high quality installer-friendly siren with a sound output of 120 dB @ 1 m, that meets today's security and environmental requirements.
The siren is housed in attractive steel cover made from UV-proof and impact resistant.
The siren has a foam-resistant steel inner cover for the ultimate protection.



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both : beacon & siren
- Choice of cut-off time

AS630

Outdoor siren with single amber beacon, inox cover

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	120 dB at 1 m (typical)

Flash specifications

Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Operating voltage	13 to 14.2 V
Current consumption	600 mA 25 mA (standby current) 110 mA (operating current)

Physical

Physical dimensions	210 x 300 x 87 mm (W x H x D)
Net weight	3 kg
Material	Inox

Environmental

Operating temperature	-25 to 55 °C
IP rating	35

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:11