# FE130MD

**Eco Line double magnetic lock, 300Kgf, monitored, surface mount**



## Details

- 2 x 300 Kgf holding power
- Monitored changeover
- No residual magnetism
- 12/24 V dc jumper selectable operation

# FE130MD

## Eco Line double magnetic lock, 300Kgf, monitored, surface mount

## Technische specificaties

### General

| | |
|---|---|
| Product type | Magnetic lock |

### Holding force

| | |
|---|---|
| Holding force kgf (Kilogram force) | 300 kgf x 2 |
| Holding force N (Newton) | 3000 N x 2 |

### Monitoring & status

| | |
|---|---|
| Monitored | Yes |
| LED indicator | Yes |
| Door status switch | No |
| Monitored changeover | Yes |
| Magnetic bond sensor | Yes |

### Electrical

| | |
|---|---|
| Power supply value | 12 / 24 VDC |
| Current consumption | 440 mA (+/- 2,5% @ 13,5 V) x 2 |

### Physical

| | |
|---|---|
| Physical dimensions | 500 × 47 × 26 mm |
| Colour | Aluminium |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57