BS120N

Battery, 12 V, 0,8 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS120N

Battery, 12 V, 0,8 Ah

Technical specifications

General

Product type	Versiegelte Blei-Säure-Batterie

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	0.8 Ah
Internal approx. resistance	50 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	0.24 A
Max. discharge current	4 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	96 x 25 x 62 mm
Net weight	0.371 kg
Shipping weight	0.371 kg
Colour	Dunkelgrau
Material	ABS
Terminal type	Wire Leads

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:53