AS631V

Outdoor Siren Inox -Vds- Red Lens + Beacon



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both : beacon & siren
- Choice of cut-off time

AS631V

Outdoor Siren Inox -Vds- Red Lens + Beacon

Technical specifications

General

Accessory group	Sirene
Type	Außensirene
Sounder output (dB @ distance)	120 dB at 1 m (typical)

Flash specifications

Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Power supply value	13 to 14.2 VDC
Current consumption	600 mA (operation) 25 mA (standby)
Battery capacity	12 V, 7.2 Ah

Physical

Physical dimensions	210 x 300 x 87 mm (W x H x D)
Net weight	3 kg
Material	Inox

Environmental

Operating temperature	-25 to +55°C
IP rating	35

Regulatory

Certification	VdS

Frequency

	1.8 to 2.8 kHz

Cut-off timer

	Preset at 3 min. Adjustable 5 min., 10 min., 20

Self-activating (with battery)

	Yes

Beacon for all types

Operating current	110 mA
Spike suppression network	Standard fitted

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 May 2026 - 17:19