DM980I-N

950 Series Manual Call Point With Isolator - Red - Plastic Housing

General

The DM980I-N is an addressable, 950 series manual call point in a durable plastic, red housing with a DIN IP42 rating. It is supplied with a built in, dual insulator and is designed for installation onto standard junction boxes. The ABS housing uses the standard EN54 house-on-fire function indicator and provides ample space for wiring.

This locking push-button-actuated call point is designed according to DIN14655 and is VdS approved (G 297059). Activation is indicated with a red LED, whilst a yellow LED indicates the status of the isolator. The door is secured by key and may be opened to more than 180°. The activation window is replaceable.

Operation

The DM980 series manual call points are designed for use with Aritech addressable fire panels running 900 series protocol.

Activation of the alarm is done by dual action:
· Breaking the glass
· Activating the push button

Resetting an alarm on the unit takes place automatically when opening and/or closing the door of the call point.

Accessories

Accessories normally supplied with the call point may also be ordered seperately.

· Replacement key (DM900KEY)
· Replacement glass (DM966)



Details

- Durable plastic ABS housing with "House-on-fire" functional indicator
- Protocol compatible with 950 series devices
- Alarm LED and dual isolator fitted
- Replaceable window
- Auto reset facility
- Door secured by key
- Conforming to DIN14655 and VdS approved

DM980I-N

950 Series Manual Call Point With Isolator - Red - Plastic Housing

Technical specifications

Electrical

Power supply type	24 VDC
Current consumption	2 mA (Alarm) 70 µA (Standby)

Physical

Physical dimensions	125 x 125 x 36 mm (W x H x D)
Net weight	225 g
Colour	Rot (RAL 3001)
Material (body)	RA6 + 30%gF
Door opening angle	>180°

Environmental

Operating temperature	-40 to +80°C
Environment	Drinnen
IP rating	IP42

Regulatory

Certification	EN54-11

Compatible products

Category	Reference	Description
Detection device	DM966	Replacement clear windows for push-button activated manual call points

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 October 2026 - 14:34