AS620RF-RC

Telecomando per AS620RF-TR-N, 868 Mhz

The AS620RF-RC is a two-way remote control with four programmable buttons to send easy remote commands to the transceiver module AS620RF-TR-N. Immediate visual feedback of the status will be provided by the 4 status LEDs, one for each output.

All the main functions of an alarm control panel can be assigned to the buttons, i.e. switching on, switching off, specific output activations, etc.

Up to 4 remote controls can be added to allow the end-user to operate his security system in a quick and easy way.

Dettagli

- Telecomando per AS620RF-TR-N
- Comunicazione wireless bidirezionale
- Fornito con due diverse grafiche dei pulsanti
- Fino a 4 telecomandi con un singolo AS620RF-TR-N
- LED di stato

AS620RF-RC

Telecomando per AS620RF-TR-N, 868 Mhz

Specifiche tecniche

Electrical

Operating voltage	3 VDC lithium battery, model CR2032

Physical

Physical dimensions	80 x 35 x 16 mm

General

Operating frequency	868 MHz
Wireless signal range	200 m
Compatability	AS620RF-TR-N

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57