# RF-DC101-K4

## Trasmettitore univerale con contatto magnetico Wireless, bianco, 433Mhz, 80plus LoNa

In this series we are using KGS's 80+ wireless protocol in a 433Mhz frequency set-up, which allows for a better wireless indoor range. This 80+ protocol helps ensure security approvals.
This wireless door window sensor, which has 2 reed switches, protects anything that opens and closes such as doors, windows and cabinets. You can monitor any supervised contact in such a way that hardwired devices become wireless in a fraction of time.
The sensor is equipped with a wall and cover tamper for additional security.
This series comes in a white and a mahogany version and also has accessories in both colors.



### Dettagli

- 80+ wireless protocol using 433Mhz for improved indoor range
- 5-years battery life
- Battery pull-tab concept
- Selectable reed switches
- Additional terminal block
- Range of accessories : two types of spacers and a stronger magnet
- Holding EN and Incert certificates

# RF-DC101-K4

## Trasmettitore universale con contatto magnetico Wireless, bianco, 433Mhz, 80plus LoNa

## Specifiche tecniche

### General

| | |
|---|---|
| Application type | Montaje en Superficie |
| Contact type | Reed switch |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Trådløs |
| Wireless frequency | 433 MHz LoNa |
| Open-air range | 400 m |

### Electrical

| | |
|---|---|
| Battery lifetime | >5 años con señal de supervisión por 15 min. y 4 activaciones/hora |

### Physical

| | |
|---|---|
| Colour | Hvid |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 2 |

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57