FA350WY

LED Visual Indicator, White Shallow Base, Yellow Lens

General

The FA350WY is a general purpose LED visual indicator for alarm applications. It features a special base containing all wiring connections and allows for easy removal/placement of the device and base.

Easy and Fast Installation

The FA350WY allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these devices use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

A mechanism for locking the devices to the base may be activated if required. Once activated, a special tool is required to remove the device from the base.

The FA350WY utilises a full faced translucent case, giving a much larger lens area and a greater spread of light.



Details

- Low current consumption
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- High efficiency LED's

FA350WY

LED Visual Indicator, White Shallow Base, Yellow Lens

Technical specifications

General

Line monitoring	Polarised input

Electrical

Operating voltage	17 to 60 VDC
Current consumption	5 mA

Sounder

Output level	Continuous operation

VID

Flash frequency	1 Hz 60 flashes/min

Physical

Physical dimensions	100 x 81 mm (Ø x D)
Net weight	215 g
Colour	Hvid, Gul / gul
Material	Polycarbonate haut impact

Environmental

Operating temperature	-25 to +70°C
Environment	Indendør
IP rating	IP21

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 February 2025 - 15:47