SC-51-0100-0001-99

SmartCell Fire Manual Call Point

Overview

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

SC-51-0100-0001-99

SmartCell Fire Manual Call Point

Technical specifications

General

Status indication	LED
Wireless frequency	868 MHz
Compatibility	SmartCell, Excellence Gateway

Electrical

Batteries	2 x 3.6 V lithium thionyl chloride batteries Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Physical

Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	Rød
Mounting type	Vægmontering

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indendør

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-11 EN54-13 EN54-25

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 May 2026 - 16:00