SMA-ICLASS-WR

SIGMA Series - Outdoor/WR/IP65, Multi-factor Bio/Card/PIN/BioPIN (3k users incl.), HID iClass, 1M logs storage capacity, PoE incl.



UNRELEASED

SMA-ICLASS-WR

SIGMA Series - Outdoor/WR/IP65, Multi-factor Bio/Card/PIN/BioPIN (3k users incl.), HID iClass, 1M logs storage capacity, PoE incl.

Especificaciones técnicas

System

RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	Yes

Technology

Reader type	Biométrique
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	iCLASS (CSN), iCLASS (données personnalisées), iCLASS SEOS
Read write	Yes
SAM module embedded	No

Biometric

Biometric type	Empreinte digitale
Biometric sensor type	Optique

Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 canal sécurisé, RS-485, USB, Wiegand
Connector type	Netzwerk, Klemmleiste

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
PIN keypad	Yes

Electrical

Power supply type	VDC

Physical

Colour	Schwarz
Material	Polycarbonat
Form factor	Überdimensioniert
Mounting type	Montage en surface

Environmental

Vandal proof	No
Environment	Drinnen, Draussen

Regulatory

Compliancy	CE, FCC, REACH, RoHS, UL 294, WEEE

UNRELEASED

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57