DI601

Outdoor PIR, selectable 10/20/30 m (33/66/98 ft)



DI601

Outdoor PIR, selectable 10/20/30 m (33/66/98 ft)

Technische specificaties

General

Technology	PIR
Application type	Fixation murale
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Detection range	30 m
Detection range selection	10, 20 or 30 m
Coverage (field of view)	70°
Undercrawl protection	No
Alarm time	5 secondes

Wired/wireless

Wired-wireless	Kablede

Inputs/outputs

Alarm relay characteristic	NC / NO, Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Relay configuration	Valeurs EOL multiples

Electrical

Power supply value	9 to 15 VDC
Current consumption	7 mA

Physical

Physical dimensions	147 × 187 × 140 mm
Net weight	306 g
Shipping weight	532 g
Colour	Sølv
Material	Høj slag ABS plast med HDPE dæksel, UV stabiliseret
Mounting height	3 à 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Udendørs

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57