ATS1187

Sicherer MIFARE DESFire EV1/EV2/EV3-Kartenleser mit Ausgang und RTE-Eingang in Standardausführung

Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel or 4 door controller using the ATS databus. Communication to Axon or Advisor Advanced control panels is AES encrypted, providing data to be securely communicated from the card to the processing unit. The readers are configured through locally through keypad and control panel menu or addressed through the ATS1482 addressing card. Select secure cards from the ATS145x secure card series.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.
The ATS Mifare Desfire EV1 readers are designed to transfer card data is a secure and reliable way in various environments. The card data is by default secured by an Interlogix own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates over the ATS LAN databus to Axon or Advisor control panels and 4 door controllers. When connected to Axon or Advisor Advanced control panels, the data between reader and control panel is AES encrypted, securing the data from the card until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.



Einzelheiten

- Sicherer ATS-MIFARE DESFire EV1/EV2/EV3-Leser
- Unterstützt Secure Mifare (Sicherheitsmodus) oder Mifare mit 4- oder 7-Byte-CSN/UID (Nicht-Sicherheitsmodus)
- Verwenden Sie Karten der sicheren ATS145x-Serie oder kundenspezifische Karten
- Sichere Kommunikation mittels AES-128-Bit-Verschlüsselung zwischen Lesegerät und Axon / Advisor Advanced / CDC4-Zentralen
- Robustes Kunststoffgehäuse in schlankem Design
- Montage im Innen- oder Außenbereich
- ATS-Bus-Schnittstelle
- Eingabe des Befehls „Request To Exit“
- Open-Collector-Ausgang (Tür offen)
- Unterstützt ab Advisor Advanced MR4.2

ATS1187

Sicherer MIFARE DESFire EV1/EV2/EV3-Kartenleser mit Ausgang und RTE-Eingang in Standardausführung

Technische Spezifikationen

System

Reading distance	Sicher: max. 2 cm Unsicher: max. 5 cm Bluetooth: abhängig vom Mobilgerät und den Einstellungen
Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Indirizzamento tessere
No. of LEDs	3

Technology

Reader type	Smartcard
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70)

Interface & connections

Interface	ATS RS-485
Connector type	Zopf
Pigtail length	2 m

Inputs/outputs

Inputs	Richiesta di uscita
Outputs	1 Open Collector (50 mA)

Tamper type

Pry-off tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Electrical

Operating voltage	10,8 bis 30 VDC
Current consumption	50 mA @13,8 VDC normal 120 mA @13,8 VDC max.

Physical

Physical dimensions	126 x 85 x 28 mm
Net weight	240 g
Shipping weight	275 g
Colour	Schwarz
Material	Plastik
Form factor	EMEA Kontaktbox
Mounting Type	Montaggio a superficie

Environmental

Operating temperature	-30 bis +55°C
Storage temperature	-30 bis +55°C
Relative humidity	<95%, nicht kondensierend
Environment	Drinnen, Draussen
IP rating	IP67 IK-09

Regulatory

Compliancy	CE

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.