AS620RF-N

Sirena esterna stand alone autoalimentata via radio compresa unità ricetrasmettitore e pacco batterie, 868 Mhz.

The AS620RF-N self-powered siren is a stand-alone two-way wireless siren for outdoor applications. It is compatible with the transceiver module AS620RF-TR-N which is included.

The siren is protected against the removal of its cover and against being removed from the wall. It has an internal polycarbonate cover. It can receive signals from the AS620RF-TR-N transceiver for alarm activation and system status. The siren will send a signal back to the transceiver in case it detects a tamper condition, supervision fault, low battery or a system fault.

Optionally, up to 4 remote controls can be added to allow the end-user to operate additional outputs through his security system in a quick and easy way.



Dettagli

- Soluzione wireless completa, inclusa sirena esterna e telecomando (opzionale)
- Soluzione wireless autonoma bidirezionale
- Pacco batterie incluso
- Doppia protezione antimanomissione: anti-apertura e anti-rimozione da una parete
- Sistema antischiuma meccanico
- Sistema anti-perforazione
- Varie opzioni di programmazione e temporizzazione
- Supervisione, manomissione, batteria scarica e indicazione di guasto
- Luce stroboscopica a LED multicolore

AS620RF-N

Sirena esterna stand alone autoalimentata via radio compresa unità ricetrasmettitore e pacco batterie, 868 Mhz.

Specifiche tecniche

General

Sounder output (dB @ distance)	105 dB at 1 m (typical)
Operating frequency	868 MHz
Cut-off timer	30 s, 60 s, 120 s, 300 s
Maximum transmission power	2 mW
Wireless signal range	500 m in open field

Electrical

Operating voltage	7.5 Vdc battery pack
Current consumption	160 µA (standby) 250 mA (alarm)

Physical

Physical dimensions	312 x 236 x 109 mm
Shipping weight	2866 g (w/o battery)

Environmental

Operating temperature	-10 to +50°C
IP rating	IP44

Regulatory

Compliancy	ROUGE (2014/53 / UE)

Prodotti compatibili

Categoria	Riferimento	Descrizione
Accessories	AS620RF-BP	Pacco batterie al litio di ricambio per AS620RF(-N), 7.5 VCC (5 x 1.5 size "D" alkaline)
Accessories	AS620RF-TR-N	Ricetrasmettitore di ricambio per sirene via radio AS620RF-N, 868 Mhz

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57