DP721T

Multi criteria optische rookmelder met thermo element op ± 60° C



DP721T

Multi criteria optische rookmelder met thermo element op ± 60° C

Technische specificaties

Electrical

Power supply type	Zone alimentate

Detection

Monitoring	Alarm threshold, Contamination level

Physical

Colour	Bianco nuvola (RAL 9001)
Mounting type	Loftmontering
Material (body)	Plastic

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	DB702	Universele montagevoet voor 700 serie rookmelders met 6 aansluitklemmen
Notification device	AI672	Nevenindicator uitgevoerd met 2 grote leds, 6-28VDC, 4 mA nominaal
Notification device	AI673	Nevenindicator voorzien van akoestische signalering middels bleeper, 2 leds

KIDDE GLOBAL SOLUTIONS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57