VE1012PI

Vector PIR, 9 curtains, 12 m, Pet Immune



Details

- Passive Infra Red motion sensor
- 3-Brid Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- 15Kg pet tolerance
- Under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- EN50131-2-2 Grade 2 certified
- Several European approvals

VE1012PI

Vector PIR, 9 curtains, 12 m, Pet Immune

Technische specificaties

General

Technology	PIR
Application type	Montagem em parede
Anti masking	No
Pet immune	Yes
Camera	No
Signal processing	Vector Verified Enhanced (VE2)
Pry-off tamper kit	ST400 (opcional)

Detection

Max. detection range	12 m
Detection range	12 m
Undercrawl protection	Yes
Alarm memory	No
Alarm time	3 sec

Wired/wireless

Wired-wireless	Kablede

Inputs/outputs

Relay configuration	Isolado ou EOL 47K7
Remote control lines	Walk test

Physical

Colour	Hvid
Mounting height	2.3 a 3 m

Environmental

Environment	Indendør

Regulatory

EN50131 grade	Lønklasse 2



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57