# GS320

## Piezo glassbreak detector with relay output 2 m



### Details

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

# GS320

## Piezo glassbreak detector with relay output 2 m

## Technische specificaties

### General

| | |
|---|---|
| Technology | Piezoelektryczny |
| Glass types | Plade |
| Range | 2 m radius |
| Tamper switch | No |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Electrical

| | |
|---|---|
| Power supply value | 9 to 18 VDC |
| Current consumption | 5 mA at 12 VDC<br>4 mA at 6 VDC |

### Physical

| | |
|---|---|
| Physical dimensions | 37 × 19 × 12 mm |
| Net weight | 50 g |
| Colour | Hvid |
| Mounting type | Montaż nawierzchniowy |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +70°C |
| IP rating | IP67 |

### Regulatory

| | |
|---|---|
| Certification | EN50131 Grad 2, VdS |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57