ATS1455

(10 stk) Mifare Desfire EV2 firkantet proxkort

Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.
When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.



Detaljer

- Attractive designed keyfob in ISO card model
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application

ATS1455

(10 stk) Mifare Desfire EV2 firkantet proxkort

Tekniske specifikationer

System

Reading distance	Secure mode: between 1 - 5 cm Unsecure mode: between 2-5 cm Distance may vary based on reader
Custom data model	No
Memory size	2K
Supported readers	ATS ATS118x Secure Readers

Technology

Credential type	Smart kort
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN)

Printing

Direct surface printing	No

Ordering information

Minimum order quantity	1
Cards/tags in package	10

Physical

Material	PVC
Form factor	Klemmeskal
Physical dimensions	86 x 54 x 9 mm
Net weight	66 g
Shipping weight	67
Colour	Hvid
Card Label	Serial number

Environmental

Operating temperature	-10 to +50°C
IP rating	IP68

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57