# SC-11-1201-0001-09

## Painel de Controlo SmartCell Wireless (s/ módulo de comunicação) - Espanha

### SmartCell overview

SmartCell has been designed as a complete wireless fire detection system to protect people and property. The system incorporates separate information zones which allow input devices to be configured in multiple configurations, providing maximum flexibility to the user and designer.

A SmartCell system can support up to 64 wireless devices consisting of 32 fire devices and 32 information devices.

Communication between devices and the control panel is bidirectional and operates in the European harmonised 868MHz frequency band.

With significant time saving against conventional and addressable fire system installations, no cables, no mess and no inconvenience to everyday business, SmartCell is perfect for all small to medium sized fire system installations.




### Detalhes

- Totalmente sem fios
- Simples e rápida instalação
- Caixa compacta
- Display OLED de 80 carateres
- Espaço interior para adicionar placa de comunicação para ligação aos Serviços SmartCell
- Disponível também em versão 24 VDC

# SC-11-1201-0001-09

## Painel de Controlo SmartCell Wireless (s/ módulo de comunicação) - Espanha

## Especificações técnicas

### General

| | |
|---|---|
| User interface | 16 Zone Indikatoren |
| Maximum system capacity (device count) | 1 bis 32 |

### Electrical

| | |
|---|---|
| Power supply type | 230 VAC |
| Operating voltage | 220 to 240 VAC, 50 Hz, 0.3 A |
| Current consumption | 5 mA (PSU), plus 100 mA from control panel |

### Zone

| | |
|---|---|
| Maximum zone capacity | up to 16 |

### Standby battery

| | |
|---|---|
| Capacity | 6 V 4 Ah |

### Physical

| | |
|---|---|
| Form factor | Kompakt |
| Physical dimensions | 275 x 220 x 80 mm (W x H x D) |
| Net weight | 1.55 kg |
| Mounting type | Oppervlaktemontage |
| Cable entries | 4 x 100 mm (bottom) / 4 x 100 mm (back) |

### Environmental

| | |
|---|---|
| Operating temperature | -5°C to +45°C |
| Storage temperature | 0°C to +30°C |
| Relative humidity | 95% noncondensing max. |
| Environment | Drinnen |
| IP rating | IP30 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-2<br>EN54-4<br>EN54-13<br>EN54-25 |

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57